


Open Frame Touch Monitor

HO 275 PTB

68,58 cm / 27" Diagonal
LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080p Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- Triple Input: DP + HDMI + VGA
- Built-in Speakers
- IP65 (front) Rating Level
- Display Protection: Thickness 3mm
- 7H Toughened Hard Panel Surface
- Built for 24/7
- VESA Mount and Multiple Mounting Options
- Edge to Edge glass without raised frame
- Orientation: Landscape, Portrait, Face-Up



68,58 cm / 27"

Part. No.: HO 275 PTB

SIZE, RESOLUTION



27" Display Size
16:9 Aspect Ratio



Full HD
1920 x 1080

CONNECTIVITY, IP LEVEL



DP
HDMI
VGA



IP 65
Water & Dust
Protection

VIEWING ANGLE, VESA



178 Ultra-Wide
Viewing Angle




VESA
Wall-Mountable

OTHER FEATURES





10 Points
Touch



Built for 24/7
Operation

Display Size	68,58 cm / 27" Diagonal
Panel Type	TFT – LED Backlight, ADS Panel (**)
Aspect Ratio	16:9
Resolution (H x V)	1920 x 1080 Full HD
Brightness	300cd/m ² Panel / 260 cd/m ² Monitor
Contrast	1.000:1 (Typical); 80.000.000:1 (Active Contrast)
Viewing Angle L/R; U/D	178° H / 178° V (CR > 10)
Response Time	5 msec
Pixel Pitch	0,311 (H) x 0,311 (V) mm
Touch Type	Projected Capacitive – 10 Point Touch Type: Cover Glass + LOCA + ITO Glass
Display Colors	16.7M Colors
Horizontal Frequency	30 ~ 83 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	1920 x 1080 @ 60Hz
Input 1	VGA
Input 2	HDMI
Input 3	Display Port
Input 4	USB 2.0 Type B (Touch)
Speakers	Yes, 2W x 2, Earphone jack
Power Consumption	On: 16,8W; Stand-by: 0,3W; Off: 0,2W
Power Range	Built-In Power Supply AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	649,2 x 47 x 387 mm (W x D x H)
Packing Dimensions	735 x 146 x 480 mm (W x D x H) TBC
Net / Gross Weight	- Kg / - Kg TBC

VESA Mounting	100 x 100 mm. Screws: M4, 12mm (Max), pitch 0,7
Display Protection	Thickness 3 mm
Hardness / Transmittance	≥7H Toughened hard panel surface / ≥ 86%
IP Rating Level	IP 65 (Front), Water and Dust Protection (*)
Controls	Power, Auto, (+), (-), Menu
Color	5500K, 6500K, 9300K, User Mode
Preset Mode	PC, Movie, Game, ECO Modes
On Screen Display	11 Languages
Accessory	Power Cable (1,5m); HDMI Cable (1,5m); USB 2.0 (B-A) Cable, for Touch (1,5m).
Orientation	Landscape, Portrait, Face-Up
24 / 7	Yes



Supplier's Name	HANNspree
Model Name	HO275PTB
Energy efficiency class for standard Dynamic Range (SDR)	D
Annual Energy Power Consumption (kWh/1000h)	17 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	16,8 W
Off mode power demand (W)	0,2 W
Standby mode power demand (W)	0,3 W
Screen Diagonal (cm / inches)	68,6cm / 27"
Resolution	1920 x 1080

PART. NO.:
HO 275 PTB



HO 275 PTB 27" Open Frame Touch Monitor

