HANNSPICE HO 550 HTB 55" Open Frame Touch Monitor

Open Frame Touch Monitor HO 550 HTB

55" / 139,7cm Diagonal LED Backlight – Format 16:9

- 1920 x 1080 Full HD 1080P Resolution
- 10-Point Touch P-Cap Technology
- 178° / 178° Ultra Wide Viewing Angle
- 5000:1 High Contrast Ratio
- Built-in Speakers
- IP65 (front) Rating Level
- Display Protection: Thickness 4mm
- ≥7H Toughened Hard Panel Surface
- Slim Profile with Narrow Edges
- VESA Mount and Multiple Mounting Options
- Orientation: Landscape, Portrait, Face-Up



55" / 139,7 cm Part. No..: HO 550 HTB



VIEWING ANGLE, TOUCH



10 POINT TOUCH 178 Ultra-Wide Viewing Angle

10 Point Touch

OTHER FEATURES



Low Power Consumption

Experts in **Display**



Stereo Speakers

Technical	Spe	ecifica	ations	

Display Solutions

HANNspree

HO 550 HTB 55" Open Frame Touch Monitor

Display Size	139,7 cm / 55" Diagonal	
Panel Type	TFT – LED Backlight	
Aspect Ratio	16:9	
Resolution (H x V)	1920 x 1080 Full HD	
Brightness	350cd/m ² Panel / 300 cd/m ² Monitor	
Contrast (Typ.)	5.000:1 (Typical)	
Display Area	1209,6(H) x 680,4(V)	
Viewing Angle L/R; U/D	178° H / 178° V	
Response Time	8 msec	
Pixel Pitch	0,63 (H) x 0,63 (V) mm	
Touch Type	Projected Capacitive Type – 10 Point Touch Material Glass + Glass	
Display Colors	16.7M Colors	
Horizontal Frequency	30 ~ 83 kHz	
Vertical Frequency	55 ~ 75 Hz	
Max Display Frequency	1920 x 1080 @ 60Hz	
Input 1	VGA	
Input 2	HDMI	
Input 3	USB Type B (Touch)	
Speakers	2 x 2W, 4 ohm	
Power Consumption	On: 120W; Stand-by: ≤0,5W; Off: ≤0,5W TBC	
AC Power Range	AC 100 ~ 240 Volt; 50 ~ 60 Hz	
Product Dimensions	1289,6 x 72 x 760,4 mm (W x D x H)	
Packing Dimensions	139 x 15,5 x 86,5 mm (W x D x H)	
Net / Gross Weight	35 Kg / 38 Kg	
Vertical Frequency Max Display Frequency Input 1 Input 2 Input 3 Speakers Power Consumption AC Power Range Product Dimensions	55 ~ 75 Hz 1920 x 1080 @ 60Hz VGA HDMI USB Type B (Touch) 2 x 2W, 4 ohm On: 120W; Stand-by: $\leq 0,5W$; Off: $\leq 0,5W$ TBC AC 100 ~ 240 Volt; 50 ~ 60 Hz 1289,6 x 72 x 760,4 mm (W x D x H)	

400 x 400 mm **VESA Mounting** Thickness 4±0.3 mm **Display Protection** Hardness / Transmittance \geq 7H Toughened hard panel surface / \geq 85% **IP Rating Level** IP 65 (Front), Water and Dust Protection * Power, Auto, (+), (-), Menu Controls Power supply; HDMI Cable (1.8m); USB Cable for Accessory Touch. Certifications CE, RoHS On Screen Display 9 Languages Orientation Landscape, Portrait, Face-Up

Experts in **Display**



* IP65: The IP Code classifies how resistant a device is to foreign objects and moisture. IP65 means that the monitor is protected from total dust ingress and it is protected against low pressure water jets from any direction. Limited ingress permitted.

© 2021 HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.